

MZQE.EX26861 - FIRE HOSE, LINED, UNCOUPLED, FOR MUNICIPAL AND INDUSTRIAL USE

Fire Hose, Lined, Uncoupled, for Municipal and Industrial Use

See General Information for Fire Hose, Lined, Uncoupled, for Municipal and Industrial Use

TECHNONET

EX26861

19 Khaleel El Arousee St
El-Higaz Sq
Heliopolis, Cairo 11361 EGYPT

Three-layer fire hose with nitrile/PVC blend rubber lining, a woven reinforcement of polyester, a nitrile/PVC blend rubber third layer. Model: *Melton*. Size: 1-1/2& 2-1/2 in. Service test pressure: 250 psi.

Fire Hose, Model: *Melton Plus*. Size: 1-1/2 and 2-1/2 inch nominal diameters. Service test pressure: 250 psi. A single-jacket hoses with an EPDM liner adhered to the woven polyester reinforcing jacket.

Last Updated on 2015-07-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"